

Chieftain < Undefined > Insulated Half Pipe Tipping Trailer |







The Chieftain Insulated Half Pipe Tipping Trailer is specially designed to transport materials such as tarmacadam with a 50mm wall of insulation. The trailer also comes with a full Hardox body which is lower in weight and higher durability than ordinary mild steel. Hence the reason for its application in this product

Vehicle Features

2 Line Air with Wabco EBS (Electronic Braking System) (EU Type Approved), 2 Speed adjustable height jacking leg with handle, 2 x LED Flashing Strobes on rear, 2" Bolt in Kingpin, 6 x 385 / 65 R 22.5 Tyres, 24 Volt single pole via ISO 12098 15 pin connector and ISO 7638 EBS connector conforming to EU regulations., Air Suspension c/w Raise/Lower Valve, Automatic Slack Adjusters, Commercial Axles 420mm x 180mm (EU Type Approved), Electric front to back cover, EU type approved Bolt on spray suppression mud flaps fitted behind each wheel., EU type approved sideguards fitted under the side raves., Front lift axle, Gross Weight: 44 Ton, Hydraulic up and over rear door, Insulated Hardox body, License plate holder with light, Load Sensing Valve / Park and Shunt Valves, Manual Roll over Cover, Mudguards fitted over wheels, Rear LED Lamp clusters with front and side LED marker lights, Safety labels fitted to trailer with conspicuity Hi-Vis Tape fitted to rear and sides of trailer, Single hydraulic tipping cylinder on front, Trailer finished in 2 Pack primer and paint, Trailer Shot blasted to guarantee high quality and longlasting resistance against corrosion

