

Chieftain <Undefined> 3 Axle Semi Low Loaders |



The Chieftain 3 axle semi low loader is a strong and robust trailer that is used for the transportation of heavy plant and machinery up to 44 ton gross

Vehicle Features

2 x LED flashing strobes on rear, 2 x Stainless steel toolboxes (one each side), 2" Bolt in kingpin, 12 x 235 / 75 R 17.5 new "J" rated tyres, 24 Volt single pole via ISO 12098 15 pin connector and ISO 7638 EBS connector conforming to EU regulations., Air locked self steering axle, Air suspension c/w Raise/Lower Valve, Aluminum neck surround, Bolt on spray suppression mud flaps fitted behind each wheel., Chassis constructed from high tensile steel, Commercial axles, Double flip hydraulic ramps, Galvanised pull-out outriggers, Galvanised T-bar overrun fitted to neck of trailer, Gross weight: 44Ton, Hydraulic straight up ramps powered via electric over hydraulic power pack, Keruing hardwood floor, Lashing rings recessed into the side chimes and on deck, Length : 13.6m, License plate holder with light, Load sensing valve / park and shunt valves, Outrigger boards and storage tray, Powerslide shift ramps, Rear LED Lamp clusters with front and side LED marker lights, Rear lift axle, Safety labels fitted to trailer with conspicuity Hi-Vis Tape fitted to rear and sides of trailer, Sideguards fitted under the side raves., Spare wheel mounted on trailer, Spring brakes fitted with automatic slack adjusters, Swing down support legs under beavertail for ramps, Trailer emergency module featuring safe parking function., Two line air with Wabco EBS (Electronic Braking System), Two speed adjustable height jacking leg with handle, Wide marker boards with LED lights

