

## Chieftain <Undefined> Midi Low Loader |



The Chieftain Commercial Midi Low Loader is available on both mechanical or air suspension. It has carrying capacities ranging up to 11.7 Tons Gross. It is an ideal truck drawn transport solution for small plant such as mini excavators and rollers

### Vehicle Features

2 line air with Wabco EBS (Electronic Braking System) incorporating ISO 7638 socket, 2 speed adjustable height jacking leg with handle, 4 x 235 / 75 R 17.5 new "J" rated tyres, 24 volt ISO standard circuit with 2 x 7 pin sockets, 50mm or 57.5mm bolt on load bearing eye, 400mm steel drop down sides, Air suspension c/w raise/lower Valve, Bed length 4.2m & beavertail length 1m, Bolt on spray suppression mud flaps fitted behind each wheel., Cheese wedge hydraulic ramp, Commercial axles, EU type approved sideguards fitted under the side rails., Fixed headboard, Front and rear outline LED marker lights, front and side LED marker lights, Full width hydraulic ramp, Gross weight: 11.7 Ton, Hydraulic ramps powered via electric over hydraulic power pack, Keruing hardwood floor, Lashing rings recessed into the side rails and on deck, LED flashing strobes, LED worklamps, License plate holder with light, Load sensing valve / park and shunt valves, rear LED lamp clusters, rear red triangular reflectors and side amber reflectors, Rear reversing camera c/w monitor, Red and yellow air suzzies supplied with trailer, Safety labels fitted to trailer with conspicuity Hi-vis tape fitted to rear and sides of trailer, Spring assisted ramps, Spring brakes fitted with automatic slack adjusters, Stainless steel toolbox on one side, Swing down support legs under beavertail for ramps, Telescopic drawbar, Trailer supplied with EU Whole Vehicle Type Approval certification, Various bed lengths available

