

## Chieftain <Undefined> Block Trailer |



The Chieftain Block Trailer has carrying capacities up to 25 Ton. The trailer is fitted on 385/65 R22.5 Super single tyres as standard and can be fitted with drop down sides

### Vehicle Features

2 Line Air with Wabco EBS (Electronic Braking System) incorporating ISO 7638 socket (EU Type Approved), 2 Speed adjustable height jacking leg with handle, 6 x 385 / 65 R 22.5 Tyres, 24 Volt ISO standard circuit with 2 x 7 pin sockets, 50mm or 57.5mm bolt on load bearing eye, Air Suspension c/w Raise/Lower Valve, Aluminium drop down sides, Bed Length 6.1m, Commercial Axles 420mm x 180mm Brakes (EU Type Approved), EU type approved Bolt on spray suppression mud flaps fitted behind each wheel., EU type approved sideguards fitted under the side rails., Fixed Headboard, Front and rear outline LED marker lights, front and side LED marker lights, Front Lift Axle, Gross Weight: 25Ton, Keruing Hardwood Floor, Lashing rings recessed into the side rails and on deck, LED Flashing strobes, LED Worklamps, License plate holder with light, Load Sensing Valve / Park and Shunt Valves, rear LED lamp clusters, rear red triangular reflectors and side amber reflectors, Rear reversing camera c/w monitor, Red and Yellow Air Suzzies supplied with trailer, Safety labels fitted to trailer with conspicuity Hi-Vis Tape fitted to rear and sides of trailer, Spring Brakes fitted with Automatic Slack Adjusters, Stainless steel toolbox on one side, Telescopic Drawbar, Trailer finished in 2 Pack primer and paint, Trailer Shot blasted to guarantee high quality and long-lasting resistance against corrosion, Trailer supplied with EU Whole Vehicle Type Approval, Various bed lengths available in 500mm increments