

Chieftain <Undefined> 3 Axle Agricultural Low Loader |



The Chieftain 3 Axle Agricultural Low Loader is used in conjunction with agricultural tractors and is designed for the economical transport of plant and equipment

Vehicle Features

8 stud axles 300mm x 90mm, 12 Volt ISO system with 7 pin plug connection, 12 x 215/75 R17.5 new "J" Rated tyres, 80mm ball towing eye, 445/45 R19.5 wide flotation tyres, 680mm wide sprung assisted ramps, Bale Rack at front, Bed length 6.5m & beavertail 1.5m, Bolt on spray suppression mud flaps fitted, Cheese wedge, Control lever to operate ramps from rear, EN8 50mm heavy duty towing eye with adjustable plate, Fixed Headboard, front and side LED marker lights., Galvanised Pull-Out Outriggers, Gross trailer weight 27 Ton, Hose pipe holder fitted to top of drawbar to keep pipes secure, Hydraulic brakes, Hydraulic jack leg, Hydraulic ramps, LED Flashing strobes, LED worklamps, License plate holder with light., Mechanical ratchet handbrake, Multi leaf spring suspension c/w equalising rockers., Outrigger boards with storage tray, Rear LED lamp clusters, Removable foot stool under the drawbar, Self tracking rear steer axle, Sideguards fitted under the side raves., Spare wheel c/w bracket, Sprung drawbar, Stainless steel toolbox, Timber floor with chequered plate & grip bars on beavertail, Tying points on trailer deck and on side, Wide marker boards c/w LED Lights