

Chieftain <Undefined> 3 Way Tipping Rail Trailer |



Content coming soon

Vehicle Features

2 x 12 Ton 8 stud Full Beam Axles, 2 x 12 volt solar panels, 3 Way Tipping Box powered by a Hydraulic Cylinder, 4 Lashing points recessed into floor, 4 Twist locks fitted to bed of trailer to accommodate ballast box, 12 volt lighting, 40mm coupling fitted to front and rear of trailer., Approved for DB netz (Germany), Approved for I-PLM-5001 (Ireland), Approved for RIS 1530 Issue 6 (UK), Auto directional LED Lamp assemblies fitted to front and rear of trailer, Battery and battery box fitted on chassis inner beam, Box Tips Left, Control switch fitted to turn lights On/Off, Each door is opened and closed for discharge via Hydraulic Cylinders, Fabricated tow pole with 1560mm eye centres, Indicator to show the brakes are on/off visible from both ends of trailer, Lamp holder fitted at front and rear, Multi - leaf spring suspension, Operated by 4 Locking Ball Joints (1 in each corner), Platform Dimensions: 5m x 2.5m, Quantity 4 - 550mm diameter (P1 profile) steel rail wheels, Rail scrapers fitted in front of each wheel, Right and to the Rear, Safety labels fitted to trailer, Trailer finished in 2 Pack primer and paint, Trailer Shot blasted to guarantee high quality and long-lasting resistance against corrosion, Two line air brakes (Air Park and Service Brake)